### **CAD-CUT<sup>®</sup> SILICONE 500**

# DURABLE SILICONE MATERIAL WITH A MATTE FINISH AND A SOFT TOUCH.

A 0.5 mm thick silicone film with a matt surface and soft feel. Enhance your textiles with this unique 3D look. Due to its blocking properties, this material is ideal for printing on sublimated polyester.



3D EFFECT 60°



#### AVAILABLE IN

50 cm x 25 m roll

#### RECOMMENDED FABRICS \* Test before application!

• 100 % Cotton

• Cotton-Polyester blends

- 100 % Polyester\*
- $\cdot$  Sublimation dyed polyester

#### **CUTTING NOTES**

Always test the cutting settings before production. The settings depend on the age of the blade used. To ensure optimum processing of the material. Minimum line thickness of 2.5 mm.

#### **APPLICATION INSTRUCTIONS**


Temperature:	150° C	
Time:	10 sec.	Repressing: 5 sec.
Pressure:	Medium (#4-6 with Hotronix®)	
Carrier:	Cold peel	

#### **MULTI-COLOR DESIGNS**

CAD-CUT® Silicone is not suitable for multi-layer applications.

#### ACCESSORIES RECOMMENDED

- Grip Cover Sheet
- Cover Sheet Non-Sticky
- EZ Weeder®, LED Weeder. LED Pin or Tweezers



#### CARE INSTRUCTIONS

Washable up to 60° C. Please do not use fabric softener or bleach. Wash inside out and iron.

#### STORAGE

Store in a cool, dry environment. Avoid direct heat or sunlight.



500

150° C 10 sec

## **CAD-CUT<sup>®</sup> SILICONE 500**

