
















# SOFT METALLIC HEAT TRANSFER MATERIAL FEATURES A DISTINCT LUSTER AND SHINE

Creates a soft, metallised finish for textile decoration. It is supplied on a self-adhesive polyester carrier





#### **AVAILABLE IN**

50 cm x 25 m roll

### RECOMMENDED FABRICS \* Test before application!

· Cotton-Polyester blends

- · 100 % Polyester\*

· 100 % Cotton

· Sublimation dyed polyester\*

# **CARE INSTRUCTIONS**

Washable up to 40° C. Please do not use fabric softener or bleach. Suitable for tumble drying on a gentle setting. Wash and iron inside out.

## **STORAGE**

Store in a cool, dry environment. Avoid direct heat or sunlight.

# **CUTTING NOTES**

Test the cut before each production run. The blade settings must be adjusted if the blade is older. For optimum cutting and weeding: Minimum line thickness of at least 1,5 mm (1/16).

### **APPLICATION INSTRUCTIONS**

Temperature: 150° C Time: 10 sec.

Pressure: Medium (#4-6 with Hotronix®)

Carrier: Cold peel

# **MULTI-COLOR DESIGNS**

Press the background for 2 - 4 seconds - peel off the carrier warm / cold. Repeat this for additional colors. Press on the last color for 13 - 15 seconds. Remove the carrier cold.

#### **ACCESSORIES RECOMMENDED**

- · Grip Cover Sheet
- · Cover Sheet Non-Sticky
- EZ Weeder®, LED Weeder. LED Pin or Tweezers







inside out



Stretchable

















# **CAD-CUT® SOFT METALLIC**



